




17 Inch PCAP Touchscreen Monitor

Projected Capacitive Touch screen, Multi Touch, 6mm Tempered Glass Cover, Anti Glare, Anti Reflective with UV. Surface IP65 Waterproof
LCD Resolution 1280*1024, Brightness 1000cd/m2, VGA/DVI/HDMI, USB Touch, 12V DC.
Light dimming sensor. Cooling fans.



Model Number	SKT-170H-CFF03.4	
Total parameter	Diagonal Size	17.0" a-Si TFT-LCD, LCM
	Aspect Ratio	5:4
	Enclosure Color	Black
	Video Input	VGA/DVI/HDMI
	Speakers	Optional
Mechanical	Monitor Dimensions	397.2×332.5×40mm
	VESA Holes (mm)	75×75mm,100×100mm
LCD Panel	Active Area(mm)	338.92(W)×271.34(H) mm
	Resolution	1280(RGB)×1024, SXGA
	Dot Pitch(mm)	0.088×0.264 mm (H×V)
	Viewing angle(Typ.)(CR≥10)	85/85/80/80 (Typ.)(CR≥10)
	Contrast (Typ.) (TM)	1000:1 (Typ.) (TM)
	Brightness (typical)	LCD Panel: 1000 nits
		PCAP: 880 nits
	Response Time (Typ.)(Tr/Td)	3.8/1.2 (Typ.)(Tr/Td)
	Support Color	16.7M 72% NTSC
	Backlight MTBF(hr)	9S4P WLED , 30K hours
Touchscreen	Touch Technology	PCAP Touch, Capacitive Touch Screen Anti Glare+ Anti Reflective+Anti UV
	Input Methods	Finger, Gloved hand, Passive stylus
	Number of Touches	Single - Touch and 10 Multi Touch
	Glass Thickness	6mm Tempered Glass
	Light Transmission	88%
	Response Time	8 ms
	Life Span	Over 50 million touches in one location
	Positional Accuracy	± 1.5mm
	Touch interface	USB
		RS232(Optional)
	Operating System	Windows XP
		Windows 7
		Windows 10
		Linux
		Android
Power	Power Consumption (W)	DC 12V /5A ,DC head 5.0x2.5MM
	Input Voltage	100-240 VAC, 50-60 Hz
	MTBF	50000 hr at 25°C
Environment	Operating Temp.	-20～70°C
	Storage Temp.	-20～70°C
	Operating RH:	20%～80%
	Storage RH:	10%～90%
Accessories	Packing List	1 × Power Adapter, 1 × Power Cable
		1 × USB Cable, 1 × HDMI Cable
		Rear Mount brackets
Warranty	Warranty Period	1 Year Free Warranty
	Technical Support	Lifetime
Certificate	Lab Approval	CE, EMC

