

19 Inch High Brightness Open Frame LCD Monitor

LCD Resolution 1280*1024, Brightness 1000cd/m2, VGA/DVI, 12V DC
Based LCD Panel M190ETN01.0

Specifications

Model Number	SKT-190H-CFF03.5	
Total parameter	Diagonal Size	19.0" a-Si TFT-LCD, LCM
	Aspect Ratio	5:4
	Enclosure Color	Galvanized Steel
	Video Input	VGA/DVI
	Speakers	Optional
Mechanical	Monitor Dimensions	429×327×41 mm
	VESA Holes (mm)	75×75mm,100×100mm
LCD Panel	Active Area(mm)	376.32(W)×301.06(H) mm
	Resolution	1280(RGB)×1024, SXGA
	Dot Pitch(mm)	0.088×0.264 mm (H×V)
	Viewing angle(Typ.)(CR≥10)	85/85/80/80 (Typ.)(CR≥10)
	Contrast (Typ.) (TM)	1000:1 (Typ.) (TM)
	Brightness (typical)	LCD Panel: 1000 nits
	Response Time (Typ.)(Tr/Td)	3.8/1.2 (Typ.)(Tr/Td)
	Support Color	16.7M 72% NTSC
	Backlight MTBF(hr)	WLED, 30K hours
Power	Power Consumption (W)	48W
	Input & Voltage	DC 12V /5A & 100-240 VAC, 50-60 Hz
	MTBF	50000 hr at 25°C
Environment	Operating Temp.	-0～50°C
	Storage Temp.	-20～60°C
	Operating RH:	20%～80%
	Storage RH:	10%～90%
Accessories	Packing List	1 × Power Adapter, 1 × Power Cable
		1 × VGA Cable
Warranty	Warranty Period	1 Year Free Warranty
	Technical Support	Lifetime

