

## SKT-215H-CFK03

*21.5" Industrial Open-Frame Touch Monitor*

*PCAP Touch screens 3mm tempered water-proof &vandal-proof 10 touch points*



***SELENIKO 03, S.L.***

***PUBLISHED DATE:2020-05-28***

## Open Frame Touch Monitor Parameters

| Display Specifications       |               |                            |                                                 |                        |
|------------------------------|---------------|----------------------------|-------------------------------------------------|------------------------|
| Characteristic               |               | Value                      |                                                 | Comment                |
| LCD Size/Type                |               | 21.5” a-Si TFT-LCD         |                                                 |                        |
| Aspect Ratio                 |               | 16:9                       |                                                 |                        |
| Active Area                  |               | Horizontal                 | 476.64 mm                                       |                        |
|                              |               | Vertical                   | 268.11 mm                                       |                        |
| Pixel                        |               | Horizontal                 | 0.24825                                         |                        |
|                              |               | Vertical                   | 0.24825                                         |                        |
| Panel Resolution             |               | 1920(RGB)×1080 (FHD)(60Hz) |                                                 | Native                 |
| Display Color                |               | 16.7 Million               |                                                 | 6-bits + Hi-FRC        |
| Contrast Ratio               |               | 1000:1                     |                                                 | Typical                |
| Brightness                   |               | 250 nits                   |                                                 | Typical                |
| Response Time                |               | 14 ms                      |                                                 | Typical                |
| Viewing Angle                |               | Horizontal                 | 178                                             | Typical                |
|                              |               | Vertical                   | 178                                             |                        |
| Video Signal Input           |               | VGA and DVI and HDMI       |                                                 |                        |
| Physical Specifications      |               |                            |                                                 |                        |
| Dimensions                   |               | Width                      | 515 mm                                          |                        |
|                              |               | Height                     | 310 mm                                          |                        |
|                              |               | Depth                      | 44.9mm                                          |                        |
| Weight                       |               | Net Weight 7 kgs           | Shipping Weight 9.5 kgs                         |                        |
| Box Dimensions               |               | Length                     | 660 mm                                          |                        |
|                              |               | Width                      | 440 mm                                          |                        |
|                              |               | Height                     | 180 mm                                          |                        |
| Electrical Specifications    |               |                            |                                                 |                        |
| Power Supply                 |               | DC 12V 4A                  |                                                 | Power Adapter Included |
|                              |               | 100-240 VAC, 50-60 Hz      |                                                 | Plug Input             |
| Power Consumption            |               | Operating                  | 38 W                                            | Typical                |
|                              |               | Sleep                      | 3 W                                             |                        |
|                              |               | Off                        | 1 W                                             |                        |
| Touch Screen Specifications  |               |                            |                                                 |                        |
| Touch Technology             |               |                            | Project Capacitive Touch Screen 10 Touch Point  |                        |
| Touch Interface              |               |                            | USB (Type B)                                    |                        |
| OS Supported                 | Plug and Play |                            | Windows All (HID) ,Linux (HID) (Android Option) |                        |
| Driver                       |               |                            | Driver Offered                                  |                        |
| Environmental Specifications |               |                            |                                                 |                        |
| Condition                    |               |                            | Specification                                   |                        |
| Temperature                  |               | Operating                  | -10° C ~+ 50° C                                 |                        |
|                              |               | Storage                    | -20° C ~ +70° C                                 |                        |
| Humidity                     |               | Operating                  | 20% ~ 80%                                       |                        |
|                              |               | Storage                    | 10% ~ 90%                                       |                        |
| MTBF                         |               |                            | 30000 Hrs at 25° C                              |                        |

### Warranty and Components

1 Year Free Warranty for Monitor and all components.

USB Cable \*1 Pcs,

VGA Cable \*1 Pcs,

Power Cord with Switching Adapter \*1 Pcs,

Bracket\*2 Pcs

RS232 Cable & DVI Cable Sold Separately



### Mechanical Drawing



