

21.5 Inch High Brightness Open Frame LCD Monitor

LCD Resolution 1920*1080, Brightness 1000cd/m2, VGA/DVI, 12V DC
Based LCD Panel GV215FHM-N10

Specifications

Model Number	SKT-215H-CFK03.6	
Total parameter	Diagonal Size	21.5 inch a-Si TFT-LCD, LCM
	Aspect Ratio	16:9
	Enclosure Color	Galvanized Steel
	Video Input	VGA/DVI
	Speakers	Optional
Mechanical	Monitor Dimensions	500.4×295.2×50.26mm
	VESA Holes (mm)	75×75mm, 100×100mm
LCD Panel	Active Area(mm)	476.64(H)×268.11(V) mm
	Resolution	1920(RGB)×1080 [FHD]
	Dot Pitch(mm)	0.098×0.294 mm
	Viewing angle(Typ.)(CR≥10)	89/89/89/89 (Typ.)(CR≥10)
	Contrast (Typ.) (TM)	3000:1 (Typ.) (TM)
	Brightness (typical)	LCD Panel: 1500 nits
	Response Time (Typ.)(Tr/Td)	18ms (Typ.)(Tr/Td)
	Support Color	16.7M , 72% (CIE1931)
	Backlight MTBF(hr)	WLED, 50K hours
Power	Power Consumption (W)	46W
	Input & Voltage	DC 12V /5A & 100-240 VAC, 50-60 Hz
	MTBF	50000 hr at 25°C
Environment	Operating Temp.	0～50°C
	Storage Temp.	-20～60°C
	Operating RH:	20%～80%
	Storage RH:	10%～90%
Accessories	Packing List	1 × Power Adapter, 1 × Power Cable
		1 ×VGA Cable
		Rear Mount brackets
Warranty	Warranty Period	1 Year Free Warranty
	Technical Support	Lifetime

