

SKT-215H-CFK03-1500

21.5 INCH OPEN FRAME PCAP TOUCHSCREEN MONITOR

21.5 inch Capacitive Touch screen 10 Touch Point IP65 & Front Water proof, 4mm Thickness Tempered Glass Cover
FHD Resolution 1920x1080, Brightness 1500cd/m2 with cooling fans.
VGA/DVI/HDMI, USB Touch, DC 12V Power Supply



- **PCAP TOUCHSCREEN MONITOR AVAILABLE IN 8" TO 75" SIZES**
- **WITH HIGH-PERFORMANCE COMPUTING AND GRAPHICS**
- **SURFACE STRUCTURE DUSTPROOF CAN MEET IP65 STANDARD**
- **WITH 4MM TEMPERED GLASS VANDAL-PROOF STABLE AND POWER**
- **TOUCH SUPPORT LINUX / ANDROID / WINDOWS OPERATION**
- **PCAP TOUCH SCREENS MULTI 10 POINTS TOUCH**
- **CUSTOMIZED FEATURES AVAILABLE**

PUBLISHED DATE:2024-03-18

Specifications		
Model Number		SKT-215H-CFK03-1500
Total parameter	Diagonal Size	21.5 inch a-Si TFT-LCD, LCM
	Aspect Ratio	16:9
	Enclosure Color	Black
	Video Input	VGA/DVI/HDMI
	Cooling Fans	2 pcs
	Speakers	Optional
Mechanical	Monitor Dimensions	520x315x44.9mm
	VESA Holes (mm)	75x75,100x100
LCD Panel	Active Area(mm)	477.64(H)×269.11(V) mm
	Resolution	1920(RGB)×1080 [FHD]
	Dot Pitch(mm)	0.098×0.294 mm
	Viewing angle(Typ.)(CR≥10)	89/89/89/89 (Typ.)(CR≥10)
	Contrast (Typ.) (TM)	3000:1 (Typ.) (TM)
	Brightness (typical)	LCD Panel: 1500 nits PCAP: 1400 nits
	Response Time (Typ.)(Tr/Td)	13/5 (Typ.)(Tr/Td)
	Support Color	16.7M , 72% (CIE1931)
	Backlight MTBF(hr)	WLED [15S4P] , 50K hours
	Touchscreen	Touch Technology
Input Methods		Finger Gloved hand Passive stylus
Number of Touches		Single - Touch and 10 Multi Touch
Glass Thickness		4mm Tempered Glass
Light Transmission		90%
Response Time		8 ms
Life Span		Over 50 million touches in one location
Positional Accuracy		± 1.5mm
Touch interface		USB RS232(Optional)
Operating System		Windows XP Windows 7 Windows 8 Linux Android
Power	Power Consumption (W)	DC 12V /10A ,DC head 5.0x2.5MM
	Input Voltage	100-240 VAC, 50-60 Hz
	MTBF	50000 hr at 25°C
Environment	Operating Temp.	-20~70°C
	Storage Temp.	-20~70°C
	Operating RH:	20%~80%
	Storage RH:	10%~90%
Accessories	Packing List	1 x Touch Monitor
		1 x Power Switching Adapter
		1 x Power Cable
		1 x USB Cable
		1 x HDMI Cable
Warranty		Rear Mount brackets
	Warranty Period	1 Year Free Warranty
	Technical Support	Lifetime