


SKT-215H-CFK03-PVR

21.5 Inch Capacitive Open-Frame Touch Monitor

*Resolution FHD 1920*1080, High Brightness 1000cd/m2*

Projected Capacitive Touch screens 3mm water-proof &vandal-proof 10 touch points, Anti Glare

VGA/HDMI/USB Touch , 12V DC



Seleniko 03, S.L.

PUBLISHED DATE:2021-05-28

Parameters

Display Specifications			
Characteristic	Value		Comment
LCD Size/Type	21.5" a-Si TFT-LCD		
Aspect Ratio	16:9		
Active Area	Horizontal	476.64 mm	
	Vertical	268.11 mm	
Pixel	Horizontal	0.24825	
	Vertical	0.24825	
Panel Resolution	1920(RGB)×1080 (FHD)(60Hz)		Native
Display Color	16.7 Million		6-bits + Hi-FRC
Contrast Ratio	1000:1		Typical
Brightness	1000 nits		Typical
Response Time	14 ms		Typical
Viewing Angle	Horizontal	178	Typical
	Vertical	178	
Video Signal Input	VGA and DVI and HDMI		
Physical Specifications			
Dimensions	Width	515 mm	
	Height	310 mm	
	Depth	44.9mm	
Weight	Net Weight 7 kgs	Shipping Weight 9.5 kgs	
Box Dimensions	Length	660 mm	
	Width	440 mm	
	Height	180 mm	
Electrical Specifications			
Power Supply	DC 12V 4A		Power Adapter Included
	100-240 VAC, 50-60 Hz		Plug Input
Power Consumption	Operating	38 W	Typical
	Sleep	3 W	
	Off	1 W	
Touch Screen Specifications			
Touch Technology		Project Capacitive Touch Screen 10 Touch Point	
Touch Interface		USB (Type B)	
OS Supported	Plug and Play	Windows All (HID) ,Linux (HID) (Android Option)	
Driver		Driver Offered	
Environmental Specifications			
Condition		Specification	
Temperature	Operating	0°C ~+ 50°C	
	Storage	-20°C ~ +70°C	
Humidity	Operating	20% ~ 80%	
	Storage	10% ~ 90%	
MTBF	50000 Hrs at 25°C		

